

MUTINA

Homage to the square

in collaboration with The Josef & Anni Albers Foundation




EN

General information
Laying and maintenance tips
Colors
Technical features
Packing



General information

collection	HOMAGE TO THE SQUARE
design	in collaboration with The Josef & Anni Albers Foundation, 2026
production	Industrial
material	Glazed and not rectified porcelain stoneware
thickness	9 mm
nominal sizes	15·15 cm (6"-6")
specification	- 7 colours: Sea, Evergreen, Chocolate, Ice, Citron, Sage, Peach - 2 patterns: Dash, Dot - special Jolly trims available on request
patents	The Homage to the Square collection design is a Registered Community Design of Ceramiche Mutina S.p.A.
category	UNI EN 14411 Bla GL



15·15 cm
6"-6"

Laying and maintenance tips

use	Indoor walls and floors, outdoor walls
installation	Install on perfectly flat and dry floors and walls, Adapt the radii of edges and corners of the substrate.
recommended adhesive	Adhesive for porcelain stoneware
recommended joints	2 mm.
recommended fillers	<p>CEMENT-BASED GROUT: Grout 0.5 m² at a time and wash thoroughly with clean water. Remove all traces of grout carefully before it dries completely. For polished versions, a fine-grain grout must always be used.</p> <p>EPOXY GROUT: Grout 0.5 m² at a time and wash thoroughly with clean water. Remove all traces of grout carefully before it dries completely. For polished versions, a fine-grain grout must always be used.</p> <p>Download the Grout Tables</p>
cleaning at the end of installation	<p>CEMENT-BASED GROUT: Buffered acid (e.g. DETERDEK PRO by FILA or similar). Wet the floor with water, saturating the joints, and dilute the product 1:5 with water and pour it on the floor. Wait for 2-3 minutes then use a white scotch Brite pad and rinse well with clean water.</p> <p>SEPOXY GROUT: Alkaline detergent (e.g. FILA CR10 by FILA). FILA CR10: apply pure, wait for 30 minutes then use a green scotch Brite pad.</p> <p>SILICONE: Solvent for silicone e.g. FILA ZERO SIL. Put it straight onto the stain, wait for 20 minutes and remove the mark using scotch Brite.</p> <p>PAINT: Can usually be removed using water, but if resin-based paints or particular enamels have been used, it is best to ask the manufacturer which solvent is most suitable.</p> <p>RUST: stain remover es. FILA NO RUST. Apply the product onto the stain, leave for 15 minutes, remove the residue and rinse thoroughly.</p> <p>POLISHED VERSIONS: For cleaning at the end of the work, and for ordinary cleaning, we recommend limiting the use of abrasive cleaning instruments (such as iron sponges or steel scrubbing pads) as far as possible. This indication must be strictly complied with for tiles with a polished surface, because they are more vulnerable to scratching, dulling, etc.</p>
general cleaning (installed tiles)	<p>You are recommended to use ordinary neutral detergent diluted in water. Use diluted limescale-removal products in water if necessary. During ordinary cleaning it is recommended to use extremely abrasive items (such as scourers and iron or steel sponges) as little as possible. This recommendation must be adhered to rigorously in the case of tiles with a glossy surface finishing as they are more susceptible to the risk of scuffs, scratches and loss of shine, etc. In the event of heavy dirt or particularly textured surfaces, use an alkaline detergent and rinse after washing. For large surfaces, the use of a floor washing machine is recommended. During every-day cleaning procedures, it is necessary to remember that certain types of dirt (dust, sand) increase the abrasive effect of foot-traffic. Therefore we recommend that you avoid bringing in this type of dirt, which comes in from the outside, by placing a door-mat at the entrance.</p>
calibers (real size)	150x150 mm with 1 mm tolerance

Colours

7 COLOURS
2 FINISHES



Dash Ice




Dot Ice



Dash Citron



Dot Citron



Dash Sage



Dot Sage



Dash Peach



Dot Peach



Dash Sea



Dot Sea



Dash Chocolate



Dot Chocolate



Dash Evergreen



Dot Evergreen

For information about the available grouts, please contact the sales department.

Technical features

STANDARD	FEATURES	VALUE REQUIRED	HOMAGE TO THE SQUARE
ISO 10545/3	water absorption	< 0,5%	0,15%
ISO 10545/4	breaking strength	Sp> 7,5 min 1100	resistant
ISO 10545/9	thermal shock resistance	no visible alteration	resistant
ISO 10545/12	frost resistance	no visible alteration	resistant
ISO 10545/13	resistance to acids and bases	min B	A
ISO 10545/14	stains resistance	class 3	class 5
DIN EN 16165 Annex B	slip resistance	–	R10 (DOT)
DIN EN 16165 Annex A	slip resistance	–	B (DOT)
ANSI A326.3	Dynamic coefficient of friction (DCOF)		0,57 (DOT)
BS 7976-2	Slip resistance (English pendulum test)		45 dry – matt (DOT) 25 wet – matt (DOT)
UNI EN ISO 10545-7	abrasion resistance	abrasion class	from PEI 2 to PEI 5
VOC Emission			available upon request
Declaration of Contents			available upon request
EPD			available upon request
SDS			available upon request
Red List Building Materials			available upon request
BPD3			available upon request
HPD			available upon request

* Where not specified, the values of standards and certifications refer to both patterns (DOT and DASH).

Packing

SIZE	PCS-SQM	PCS-BOX	SQM-BOX	BOX-PAL	KG-BOX	KG-PAL	SQM-PAL
15-15 cm	44,44	30	0,68	51	14,15	721,66	34,68