

Z
COLLECTION



6x25 cm / 2.4"x10"
Wall tiles

White Body
6 colours

MARA

MARA

The ceramics display their beauty with the “Mara” collection. The pieces capture the eye with their contrasting forms. Some of them feature sharp lines and pronounced angles. These objects reflect light in varied facets, creating shadows and glimmers that play with the perception of space.

In contrast, others rise with soft, elegant curves, evoking the fluidity and movement of organic forms. These creations seem to have been shaped by nature itself, with undulations that invite touch and appreciation for their delicacy.

The collection offers a visual dialogue between rigidity and softness, between structure and spontaneity, creating a harmonious balance that transcends the purely visual to delve into the sensory.

La cerámica despliega su belleza con la colección “Mara”. Las piezas capturan la mirada con sus formas contrastantes. Algunas de ellas presentan líneas marcadas y ángulos pronunciados. Estos objetos reflejan la luz en facetas variadas, creando sombras y destellos que juegan con la percepción del espacio.

En contraste, otras se alzan con curvas suaves y elegantes, evocando la fluidez y el movimiento de las formas orgánicas. Estas creaciones parecen haber sido moldeadas por la naturaleza misma, con ondulaciones que invitan al tacto y al aprecio de su delicadeza.

La colección ofrece un diálogo visual entre la rigidez y la suavidad, entre la estructura y la espontaneidad, creando un equilibrio armonioso que trasciende lo meramente visual para adentrarse en lo sensorial.



COLLECTION SUMMARY	pag. 4
RESUMEN DE LA COLECCIÓN	

APPLICATIONS	pag. 5
USOS	

GET INSPIRED	pag. 6
INSPIRATE	

TECHNICAL FEATURES	pag. 24
CARACTERÍSTICAS TÉCNICAS	

PRICE CODE	pag. 25
CÓDIGO DE TARIFA	

PACKING	pag. 25
---------	---------

TECHNICAL DRAWINGS	pag. 26
DIBUJOS TÉCNICOS	

MARA 6,25x25 cm / 2.5"x10" D10



MARA CURVED 6,25x25 cm / 2.5"x10" D25



MARA ANGLED 6,25x25 cm / 2.5"x10" D25



Applications - Usos






MARA Sage Gloss - 40%, MARA **Angled** Sage Gloss - 60%



MARA **Angled** Tan Gloss - 60%, MARA **Angled** Ash Gloss - 40%





MARA Midnight Blue Matt - 40%, MARA **Curved** Midnight Blue Matt - 60%



MARA **Curved** Sage Gloss - 60%, MARA **Curved** Chalk Gloss - 40%




MARA Chalk Gloss - 25%, MARA Angled Chalk Gloss - 75%



MARA Curved Tan Matt





MARA Midnight Blue Matt - 15%, MARA Midnight Blue Gloss - 15%,
 MARA **Curved** Midnight Blue Matt - 55%, MARA **Curved** Midnight Blue Gloss - 15%





MARA Ash Matt - 50%, MARA **Curved** Ash Matt - 50%



MARA **Curved** Dijon Gloss - 50%, MARA **Curved** Chalk Gloss - 50%




Technical features for Dry-Pressed ceramic tiles with water absorption BIII (Eb >10%)			
Características técnicas para las baldosas cerámicas prensadas en seco del grupo BIII (Eb >10%)			
FEATURES / CARACTERÍSTICAS	SPECIFICATION / ESPECIFICACIÓN		NORMA
	Dimensional Features	62 mm +/- 0,75 mm x 250 mm +/- 0,75mm x 8 mm +/- 5% 62 mm +/- 0,75 mm x 250 mm +/- 0,75mm x 11,2 mm +/- 5%	UNE-EN ISO 10545-2:2019
	Water absorption	>10%	UNE-EN ISO 10545-3:2018
	Modulus of rupture and breaking strength	Thickness ≥ 7,5 mm mínimo 12 N/mm² Thickness < 7,5 mm mínimo 15 N/mm²	UNE-EN ISO 10545-4:2019
	Crazing resistance	Pass	UNE-EN ISO 10545-11:1997
	Household products resistance	GA	UNE-EN ISO 10545-13:2017
	Chemical resistance	GHA	UNE-EN ISO 10545-13:2017
	Stain resistance	>3	UNE-EN ISO 10545-14:2015
	White Body	-	-

			KG 	M2 		M2 
Modelo	Formato (cm)	Piezas / Caja	Kg / Caja	m2 / Caja	Cajas / Palet	m2 / Palet
MARA	6,25x25 cm	32	6,44 kg	0,500 m²	120	60,000 m²
MARA CURVED	6,25x25 cm	26	6,33 kg	0,406 m²	120	48,720 m²
MARA ANGLED	6,25x25 cm	26	6,18 kg	0,406 m²	120	48,720 m²

			LB 	SQ FT 		SQ FT 
Model	Format (in)	Pieces / Box	Lb / Box	sq ft / Box	Boxes / Pallet	sq ft / Pallet
MARA	2.5"x10"	32	14,20 lb	5,382 sq ft	120	645,834 sq ft
MARA CURVED	2.5"x10"	26	13,96 lb	4,370 sq ft	120	524,42 sq ft
MARA ANGLED	2.5"x10"	26	13,63 lb	4,370 sq ft	120	524,418 sq ft

Price code - Código de tarifa

MODEL / MODELO	PRICE CODE / CODIGO TARIFA
MARA	D10
MARA CURVED	D25
MARA ANGLED	D25



WAREHOUSING
In order to guarantee the characteristics of the finish the product must be kept in its original packaging until the time of fixing. If the product is likely to be stored for a long period of time it should be suitably covered.

TILE FIXING
To ensure the products adhere correctly to the surface, it is essential to use specific adhesive and grouting material. This must also be suitable for the environment they will have to withstand. Fitting with traditional mortars does not ensure good adhesion.

Due to the nature of the material there may be dimensional variations between pieces. Therefore , all types of joints must be planned and carried out correctly: structural, perimeter, expansion and installation joints. Fitting tiles without joints is not advisable from any technical point of view as this may lead to various problems.

MAINTENANCE AND CLEANING
Once the materials have been fitted, it is advisable to remove any remaining adhesive and grouting material by using a commercial descaling product designed especially, diluted with water . The descaling product must not remain in contact with the surface to be cleaned for more than 5 minutes.

As a general guideline, powder detergents should not be used, not wire wool or abrasive materials. Generally a sponge will be sufficient with warm water and liquid neutral soap. Then rinse with plenty of clean water.

ALMACENAMIENTO
Para garantizar las características de su acabado, el producto debe mantenerse en su embalaje original hasta el momento de la colocación. Si el producto va a permanecer almacenado durante un largo periodo es conveniente hacerlo bajo cubierta.

COLOCACIÓN
Para garantizar una buena adhesión al soporte es necesaria la utilización de materiales de agarre y de rejuntado adecuados al ambiente al que vayan a estar sometidos. La colocación con morteros tradicionales no garantiza una buena adhesión.

Debido a la naturaleza del material pueden existir diferencias dimensionales entre piezas. Por ello deberán planificarse y ejecutarse correctamente todo tipo de juntas: estructurales, perimetrales, de dilatación y de colocación. La colocación sin juntas es desaconsejable desde cualquier punto de vista técnico, pudiendo ser el origen de diversas patologías.

MANTENIMIENTO Y LIMPIEZA
Finalizada la puesta en obra se recomienda eliminar los restos de materiales de agarre y rejuntado con un desincrustante comercial diseñado expresamente para baldosas cerámicas, rebajado con agua, permaneciendo en contacto con la superficie a limpiar no más de 5 minutos.

Como norma general no deben utilizarse detergentes en polvo ni estropajos metálicos o abrasivos. Generalmente será suficiente con una esponja, agua tibia y un jabón líquido neutro. Posteriormente aclarar con abundante agua limpia.

Z

COLLECTION

zcollection.com

