



The Tex series blends concrete with textures that recall natural fabrics, creating a subtle textile look. The richness of the line comes from the color palette; each color includes multiple tones that give it depth and complexity. This series is modern yet warm and inviting.



Juta (Brown/Taupe)



Khadi (Beige)



Shantung (White)



Satin (Greige)



Velvet (Charcoal)

Colors are intended as a guide only and may vary from actual tile. Sizes listed are nominal. Please check samples before making final selection and to get actual dimensions for layout. See reverse side for additional product information.

## Colors

Juta (Brown/Taupe)	PSTXJA
Khadi (Beige)	PSTXKI
Satin (Greige)	PSTXSN
Shantung (White)	PSTXSG
Velvet (Charcoal)	PSTXVT

## Size (Rectified)

12 x 24	PSTX--/1224
---------	-------------

## Trim

The surface bullnose is made from field tile that is cut, ground and reglazed.

3 x 24 Surface Bullnose	PSTX--/SBN
-------------------------	------------

## Usage

Tex is suitable for residential and light to moderate commercial applications.

## Installation

It is important to blend tile within each carton and from multiple cartons during installation, as well as changing the orientation of pieces with similar graphics to attain a proper mix.

Most Italian manufacturers recommend a maximum offset of 8" (20 cm) on all large format tiles when setting a running bond. Please refer to ANSI requirements for setting large format tiles, ANSI A 108.2 section 4.3.8. Using a leveling system can improve the installation of this product.

### Non-stock sizes (Rectified)

For projects that meet minimum quantities  
Available in all colors

24 x 24	PSTX--/2424
24 x 48	PSTX--/2448
36 x 36	PSTX--/3636

## Physical Properties

Physical Properties	Norms	Value
Flexion Resistance	10545-04	$R \geq 35 \text{ N/mm}^2$ (average value)
Water Absorption	10545-03	$\leq 0,05$
Frost Resistance	10545-12	Resistant
Slip Resistance	DIN 51130 DIN 51097	R10 A
** Dynamic (DCOF) Coefficient of Friction	DCOF	Wet $\geq 0.42$



\*\* These results are for the natural finish and for the normal productions; if there is concern about a particular production, it should be tested. The Coefficient of Friction is a general guide only. Testing may vary with different production runs and with different testing labs.

As noted in the Americans with Disabilities Act (ADA) the coefficient of friction varies considerably due to facts not under the control of entities such as the manufacturers and distributors. These factors include, but are not limited to, contaminants, slope of terrain, drainage conditions, adjacent surfaces, etc. Suitability for any installation can only be determined by a site examination of all conditions that could affect the slip resistance of the tile being installed. Continual cleaning and maintenance must be performed once the tile has been installed.

# Z

COLLECTION

MADE IN ITALY

TSPSTX/200714